

MILLER FLAT GLASS WASHERS

SPECIFICATION TABLE

Model Number	Nominal Width	Brushes	Brush Drive	Roll Drive	Blower Drive	Pumps	Tank Size	Heaters	Power Req'd		----- Machine -----		
									220V	440V	Length	Height	Weight
486	48"	6 @ 4" Dia.	3 HP	1/3 HP	7.5 HP	3/4 HP	40 Gal.	2 @ 18 kw	100A	50A	11'	42"	3,550 LB
606	60"	6 @ 6" Dia.	3 HP	1/3 HP	10 HP	3/4 HP	60 Gal.	2 @ 18 kw	140A	70A	14'	48.5"	6,600 LB
846	84"	6 @ 8" Dia.	5 HP	1 HP	25 HP	3/4 HP	80 Gal.	4 @ 15 kw	236A	118A	18'	48.5"	8,500 LB
848	84"	8 @ 8" Dia.	2 @ 5HP	1 HP	25 HP	3/4 HP	80 Gal.	4 @ 15 kw	252A	126A	19'	48.5"	9,400 LB
966	96"	6 @ 8" Dia.	5 HP	1 HP	25 HP	3/4 HP	80 Gal.	4 @ 15 kw	236A	118A	18'	48.5"	9,500 LB
968	96"	8 @ 8" Dia.	2 @ 5HP	1 HP	25 HP	3/4 HP	80 Gal.	4 @ 15 kw	252A	126A	19'	48.5"	10,400 LB

ARRANGEMENTS AVAILABLE

ARRANGEMENT	CONTROLS	BLOWER	TANKS
B	RIGHT	RIGHT	LEFT
C	LEFT	RIGHT	LEFT
F	LEFT	LEFT	RIGHT
G	RIGHT	LEFT	RIGHT

OPTIONS SUFFIX:

(ARRANGEMENT)(BLOWER LOCATION)(PREWASH/FLOOD TUBE)(DI WATER)

(VAR. SPD FOOT CNTRL)(STATIC BAR)

T' = BLOWER on TOP

D' = DEIONIZED WATER

P' = PREWASH

V' = VARIABLE SPEED FOOT CONTROL

F' = FLOOD TUBE

S' = STATIC BAR

EXAMPLE: MODEL #846CTPDVS

Controls & Tanks on Left, Blower on Right Top, Prewash, DI Water Option, Var. Spd Foot Cntrl, & Static Bar.